

## LITHIUM BATTERIES



Cell size references: AA

### Electrical characteristics

(Stored for one year or less)

◉ Nominal Capacity (3mA to 2.0V, at 25°C)	1100mAh
◉ Nominal voltage	2.9V
◉ Max continuous discharge current	100mA
◉ Max. Pulse current Current value is obtaining 2.0V cell voltage when pulse is applied for 15 seconds at 50% discharge depth at 25°C	200mA
◉ Storage temperature	-60°C ~ 30°C
◉ Operating temperature	-54°C ~ 65°C
◉ Weight(approx)	20g

#### WARNING:

Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above 90°C, incinerate or expose contents to water.

## WR 14505 2.9V 1100mAh

lithium sulfur dioxide batteries (Li/so2)

### Key features

- High and stable operating voltage
- Low self-discharge rate  
Less than 1% after 1 year of storage at 20°C
- Stainless steel container
- Hermetic glass-to-metal sealing
- Non-flammable electrolyte
- Compliant with IEC 86-4 safety standard
- Non-restricted for transport

### Main applications

- TPMS
- Alarms and security system
- Memory back-up
- Tracking system
- Automotive electronics
- Professional electronics
- Computer real-time clocks


.....

**LITHIUM BATTERIES**

**WR 14505**

lithium sulfur dioxide batteries(li/so2)

**Dimensions:**



Unit: mm

Available Terminations	
-/P	Axial Pin
-/T /PT2	Radial Pin
-/PT /TP	Polarized Tab

**Typical discharge at 25°C**

